



PRESS RELEASE 2008

The RSM Roadside mower

KUHN and landscape management

The KUHN range of equipment for landscape management has just grown with the launch of a new roadside mower. Particularly for use with low power tractors, the RSM completes the present SPRING-LONGER range. At 1.80 m wide, the RSM has been developed for jobs such as management of roadside verges, field edges or grassy areas.

Qualities that make the difference

The new specifications of the RSM roadside mower are the result of our experience in design of landscape management equipment:

- **Built for “public works”:** The structural elements are built of non-tubular material which will withstand high stress or strain. For ensured reliability, joints are mounted on honeycomb wear rings and the shafts are stopped from rotating.
- **Effective cutter-bar:** Specially shaped body, forward positioned sensor roller for perfect ground following, Hardox[®] steel protective skids, anti-wrap deflectors to give the best protection for the rotor bearings, all contribute to a greater cutting capability.
- **“Go-anywhere” arm:** The mower unit hydraulic lift automatically compensates for unevenness of the verge, allows cutting above the road level and work down in a ditch. To deal with all working conditions, the cutter bar can swivel between -55° in a ditch and +90° on an embankment.

All equipment as standard

The RSM180 roadside mower comes with all equipment as standard.

- A Ø160 mm rear roller with removable ends and protected reinforced bearings.
- Double skin body.
- Mechanical safety breakaway system.
- Automatic belt tensioning.